

Features

- ▶ Robust design
- ▶ Low current consumption
- ▶ Easy to install
- ▶ Maximum 93dB(A) @ 1 metre (Tone 1)
- ▶ 32 user-selectable tones and 3 user-selectable volumes
- ▶ Lockable cap available



Description

The CSB-E is platform type sounder, which will accept the CDX Range of detectors mounted with an appropriate base*. The improved electronics result in a very low current consumption with a high sound output. A set of DIP switches are used to select the unit's tone and sound output (three settings, LOW, MEDIUM and HIGH).

| | | | |
|-------------------------------|---|---------|---------|
| Ordering Codes | CSB-E | | |
| | CSB-E(WHT) | | |
| | CS/CAP Lockable Cap | | |
| Sound Level | LOW | MEDIUM | HIGH |
| Sound Output @ 1 metre Tone 1 | 87dB(A) | 90dB(A) | 93dB(A) |
| Current Consumption @ 24Vd.c. | 6mA | 8mA | 10mA |
| Voltage Range | 18 – 30Vd.c. | | |
| Number of Tones | 32 | | |
| Operating Frequency | 440Hz – 2900Hz | | |
| IP Rating | IP21C | | |
| Operating Temperature Range | -20°C to +70°C | | |
| Compatible CDX Detectors | SLR-E3N, DCD-AE3, DCD-CE3, DFJ-AE3, DFJ-CE3 | | |
| Compatible CDX Bases* | YBN-R/6, YBO-R/6PA, YBO-R/6R, YBO-R/6RN, YBO-R/6RS, YBN-R/6SK | | |
| Colour | Ivory or White | | |
| Weight (g) / Dimensions (mm) | 110 / 116 diameter x 25 height | | |