

Features

- ▶ Robust design
- ▶ Low current consumption
- ▶ Easy to install
- ▶ Maximum 113dB(A) @ 1 metre (Tone 15)
- ▶ 32 user-selectable tones
- ▶ Utilises high intensity LED technology
- ▶ Shallow or Deep base available



Description

The CWSB-E is a conventional wall sounder beacon with improved electronic design which enables very low current consumption whilst providing a range of tones and volumes – selectable from the DIL switches on each unit. The unit is supplied with its own base, a shallow base (IP43) or a deep base (IP65). Other lens colours are available upon request.

Ordering Codes	CWSB-E(RED)		
	CWSB-E(WHT)		
Sound Level	LOW	MEDIUM	HIGH
Sound Output @ 1 metre	88dB(A)	103dB(A)	109dB(A)
Current Consumption @ 24Vd.c.	≤11mA	≤19mA	≤37mA
Voltage Range	18 – 35Vd.c.		
Number of Tones	32		
Operating Frequency	440Hz – 2900Hz		
IP Rating	IP43 (IP65 for deep base model)		
Operating Temperature Range	-20°C to +70°C		
Colour	Red, Ivory or White		
Weight (g)	110		
Dimensions (mm)	93.6 diameter x 86.6 height (shallow base model)		
	93.0 diameter x 106.9 height (deep base model)		